

P-1A

Partek Particle Testing

P-1A Partek is used to locate cracks open to the surface in porous materials, such as unfired clayware, concrete, and certain fired ceramics.

COMPOSITION

P-1A Partek is a green fluorescent material in a petroleum base.

PRECLEANING

The parts to be inspected must be free of grease, oil and dirt, and dry (free of water) prior to P-1A Partek inspection. The precleaning can be accomplished with solvents or water based detergents. If water based detergents are used, the parts must be rinsed with clean water and thoroughly dried.

METHOD OF APPLICATION

P-1A Partek may be applied to inspection parts by pressure spray, flow on or dipping. P-1A must be continuously agitated because the particles will settle out of the solution. Once P-1A is applied, it will penetrate the absorbent body, and the inspection may take place immediately.

INSPECTION

On many surfaces the particle concentration at the crack site is detectable in white light. However, for maximum detectability a black light under ultraviolet radiation of 365 nm, such as the Magnaflux EV6000, is recommended.

POST CLEANING

After P-1A Partek inspection is completed, P-1A may be removed from the test parts with solvents or water based detergents.



PART NUMBERS & PACKAGING

Packaging	Country of Origin	Part Number
5 gallon pail	United States	01-8114-40
55 gallon pail		01-8114-45

HEALTH AND SAFETY

Review all relevant health and safety information before using this product. For complete health and safety information, refer to the product Safety Data Sheet, which is available at www.magnaflux.com.